








XCK-J型系列

XCK-J	XCK-S model double insulation, according to CENELEC EN50041				
	Metal head direct-acting type	Steel-roller direct-acting type	Thermoplastic roller tumbler direct-acting type	Adjustable length and thermoplastic roller tumbler type	Thermoplastic cylindrical tumbler type Diameter=6mm length=200mm
 2-pole contact terminal Quick  2-pole contact terminal Slow off					
Machine life (million times)	30	25	30	30	30
(m/s) Motion speed (m/s)	0.5	1	1.5	1.5	1.5
Protection degree	IP667				
Rated work characters	ALTIPAK AC 15; A 300 (U _e =240V _e =3A, V _{ALTIVAR} DC 13; Q 300 (U _e =250V _e =0.27A)				
Boundary dimensions: width × depth × height	40 × 44 × 77				
Complete switch (2 poles 1-close+1-open, quick)	XCK-J161 ⇄	XCK-J167 ⇄	XCK-J10511 ⇄	XCK-J10541	XCK-J10559
Complete switch (2 poles 1-close+1-open, Cut off at first, then connect, cut off slowly)	—	XCK-J567 ⇄	XCK-J50511 ⇄	XCK-J50541	—
Shell (2 poles 1-close+1-open, quick)	ZCK-J1 ⇄	ZCK-J1 ⇄	ZCK-J1 ⇄	ZCK-J1 ⇄	ZCK-J1 ⇄
Shell (2 poles 1-close+1-open, Cut off at first, then connect, cut off slowly)	ZCK-J5 ⇄	ZCK-J5 ⇄	ZCK-J5 ⇄	ZCK-J5 ⇄	ZCK-J5 ⇄
Combination head (include executor)	ZCK-E61 ⇄	ZCK-E67 ⇄	ZCK-E05 ⇄	ZCK-E05 ⇄	ZCK-E05 ⇄
Tumbler with shifting head	—	—	ZCK-Y11	ZCK-Y41	ZCK-Y59