

Time Relay



AH2-



AH2-



ATDV-



H3BA



H3CR

Technical specification

Model	Contact	Operation	Timing range				Input voltage
			s	min	h	10h	
H3BA	Timed 2PDT	Time-limit operation/ self-resetting/ external resetting	0.05-0.5	0.5-5h			AC24 AC50V AC100/110/120 AC200/220/240V DC12V DC24V DC48V DC100V DC110V DC125V DC24V/AC240V Remark: with Z and rated voltage is universal one
H3BA-8	Timed 2PDT	Time-limit operation/ self-resetting	0.1-1	1-10h			
H3BA-8H	On-delay instant spdt	Time-limit operation/ self-resetting	0.5-5	5-50h			
H3BA-8H	On-delay instant spdt	Time-limit operation/ self-resetting	1-10	10-100h			DC24V/AC240V
H3Y-2 (ST6P-2)	Timed 2PDT	Time-limit operation/ self-resetting	0.5S 1S 5S 10S 30S 60S 120S				AC24 AC48V AC100 AC110V AC200 AC220V 240V DC12V DC24V DC48V DC100V DC110V
H3Y-2 (ST6P-4)	Timed 4PDT	Time-limit operation/ self-resetting	30Min 60Min 3H				
H5N	2PDT On-delay instant contact	Time-limit operation/ self-resetting	0.01S-100H				AC24-240V DC24V-110V
AH3	On-delay instant spdt	On-delay with instant changeover	1S-24H				240V-240V AC 24V-110V DC

Type	Contact	Operation	Time range	Coil voltage	Operating temperature	Socket fitted with	Service life		Terminal
							Mechanical	Electrical	
ASTP-N	Delay time DDDT Delay time SPDT	Time-limit operation/ self-resetting	1S-10h	24V-240V AC 24V-110V DC	-30°C - +50°C	PF-083A PF-083A-E US-08	10 ⁷	10 ⁵	Outlet solder
ASTP-Y	Delay time DDDT Delay time SPDT	Time-limit operation/ self-resetting	1S-10h	24V-240V AC 24V-110V DC	-30°C - +50°C	PF-083A PF-083A-E US-08	10 ⁷	10 ⁵	Outlet solder
ATDV- Y.N	Delay time DDDT Delay time SPDT	Time-limit operation/ self-resetting	1S-10h	24V-240V AC 24V-110V DC	-30°C - +50°C	PF-083A PF-083A-E US-08	10 ⁷	10 ⁵	Outlet solder